


PA-800


SOLID POWER AMPLIFIER



OPERATION MANUAL

OPERATING GUIDE

Front Panel




- 1. Power ON-OFF switch
- 2. Power ON indicator
- 3. Channel 2 signal indicated LED
- 4. Channel 2 clip indicated LED
- 5. Channel 2 protect indicated LED

- 6. Channel 1 protect indicated LED
- 7. Channel 1 clip indicated LED
- 8. Channel 1 signal indicated LED
- 9. Channel 1 volume control
- 10. Channel 2 volume control

OPERATION MANUAL

OPERATING GUIDE

Rear Panel




- 1. Music source input
- 2. Speaker systems terminal

- 3. AC power fuse holder
- 4. AC power supply

Connecting Guide

- Do not power on the unit until all the connections are completed.
- When the pin plug cords are employed, always connect the "White" plug to the left channel and "Red" plug to the right channel. This helps to avoid reversed connections.
- Insert the plugs firmly, poor contact will result no sounds or noise.



SPECIFICATION

Technical Specifications

Dimensions 2U Power Supply AC 110V/60Hz

Maximum Power Output 100Watts at 4 ohm Power Consumption 200W

Frequency Response 20Hz to 20 Khz(±0.5dB) Dimension(WxHxD) 430x80x290mm

Total Harmonic Distortion <0.05% (1KHz) Net Weight 11Lbs.

Signal to Noise Ratio ≥95dB Accessories Owner's manual

*Specifications are subject to change without notice.

Precautions


Be careful when open, otherwise electric shock or serious damage may be made to the product.



Unplug this product from the wall outlet when not use for a long period of time



Unplug this product from the wall outlet during lightning




Objects do not fall into the enclosure.



Arrange power cords safely. Do not hold the cord when pulling out from the wall autiet, Pull out holding plug.




This product must not touch chemicals such as benzene. Thinner or alcohol. This may result in discoloration.



Do not use this product in wet place.



This product should be installed in well-ventilated and cool place.



This product should be installed flatly and should not be shaken.



OPERATION MANUAL